Data current as of: 02-11-2026 01:42

Link to the product: https://www.ikrtech.pl/frigomilk-g9-milk-cooling-tank-with-a-capacity-of-16-000-liters-p-464.html



Frigomilk G9 milk cooling tank 16 000 l

Availability	**On order**

Product description

Frigomilk G9 milk cooling tank with a capacity of 16 000 liters

Refrigeration tank with automatic washing

Technical specifications

Construction:

- inner tank and outer cladding made of AISI 304 stainless steel;
- trapcold evaporator (registered trademark) with full primary surface and maximum efficiency;
- manhole with airtight AISI 304 cover;
- high-density eco-friendly polyurethane insulation;
- butterfly discharge valve;
- stainless steel calibrated measuring rod with litre conversion table.

Refrigeration system:

- ice-free cooling even at low fill levels;
- direct expansion system;
- available for 2, 4 or 6 milkings and compatible with pre-cooling systems and milking robots;
- remote condensing unit.

Washing system:

- automatic washing;
- low water and detergent consumption;

- high-efficiency rotating spray heads;
- stainless steel pump;
- level control for constant water quantity;
- automatic detergent selection;
- dosing pumps.

Electrical system:

- latest generation XFIC electronic control or Milk Controller FIPO1;
- 400V three-phase 50 Hz + neutral supply;
- 24V supply for control devices and solenoid valves.

Optional:

- electronic milk level sensor;
- electric heater for washing water;
- self-cleaning drain;
- heat recovery system;
- internet gateway (for XFIC).

Standards:

Compliant with EN 13732, EU Machinery Directive, LVD, EMC, PED, ISO 5708.